



HART transparent repeater

9106A

- 24 VDC supply via power rail or connectors
- Active and passive mA input
- Active or passive output via the same two terminals
- Splitter function - 1 in and 2 out
- SIL2 / SIL3 Full Assessment and certified acc. to IEC 61508



Application

- 9106A is a 1- or 2-channel isolated 1:1 repeater.
- The device supplies 2-wire SMART transmitters and can also be used for 2-wire SMART current sources. HART & BRAIN protocols are supported and are transferred bi-directionally.
- 9106A can be mounted in the safe area or in zone 2 / Class I, Division 2, Groups A, B, C, D.
- For duplication/migration purposes, the outputs can be sent to two different DCS/PLC/HMI or any monitoring system.
- In safety applications (SIL loops), the 9106AxBx can be used as a splitter with the following output configuration:
 - When using 9106AxBx in a SIL2 safety function, channel 1 is used for the safety loop. Channel 2 can be used for any non-safety device.
 - For higher safety purposes (SIL 3), 9106AxBx can be used as a splitter for SIL 3 loops. Channel 1 and 2 are then connected to the same safety PLC, where channel 2 is used as a redundant diagnostic channel (for more information, consult the FMEDA Report and the Safety Manual).

Advanced features

- The detachable displays in the PR 4500 series and the green and red front LEDs indicate operation status for each channel.
- Monitoring of error events and cable breakage on input via the individual status relay and/or a collective electronic signal via the power rail.
- Suitable for the use in systems up to Performance Level "d" according to ISO-13849.

Technical characteristics


- High galvanic isolation of 2.6 kVAC.
- Fast response time <5 ms
- High accuracy better than 0.1%.
- 2-wire transmitter supply >16 V.

Mounting

- The devices can be mounted vertically or horizontally without distance between neighbouring units.




Applications

Input signals:




Output signals:

Analog 4...20 mA Channel 1



Power connection:



Same power rail as above

Order

Type	Barrier version	Unit channels	I.S. / Ex approvals
9106A	U _o = 27.5 V : 1	Single : A	ATEX, IECEx, FM, : -
	U _o = 25.3 V : 2	Double : B	INMETRO, CCC, EAC-Ex, UKEX : -U9
			UL913, ATEX, IECEx, FM, : -KC5
			INMETRO, CCC, EAC-Ex, UKEX

Example: 9106A2B

Remember to order short-circuit bridge(s) ST9106-01 when using the 9106 with no load on the output terminals.

Environmental Conditions

Operating temperature.....	-20°C to +60°C
Storage temperature.....	-20°C to +85°C
Calibration temperature.....	20...28°C
Relative humidity.....	< 95% RH (non-cond.)
Protection degree.....	IP20
Installation in.....	Pollution degree 2 & meas. / overvoltage cat. II

Mechanical specifications

Dimensions (HxWxD).....	109 x 23.5 x 104 mm
Dimensions (HxWxD) w/ PR 4500.....	109 x 23.5 x 131 mm
Weight approx.....	250 g
DIN rail type.....	DIN EN 60715/35 mm
Wire size.....	0.13...2.08 mm ² AWG 26...14 stranded wire
Screw terminal torque.....	0.5 Nm
Vibration.....	IEC 60068-2-6
2...13.2 Hz.....	±1 mm
13.2...100 Hz.....	±0.7 g

Common specifications

Supply

Supply voltage.....	19.2...31.2 VDC
Fuse.....	1.25 A SB / 250 VAC
Max. required power.....	≤ 1.1 W / ≤ 1.9 W (1 ch. / 2 ch.)
Max. power dissipation, 1 / 2 ch.....	≤ 0.8 W / ≤ 1.2 W

Isolation voltage

Test /working: Input to any.....	2.6 kVAC / 300 VAC reinforced isolation
Analog output to supply.....	2.6 kVAC / 300 VAC reinforced isolation
Status relay to supply.....	1.5 kVAC / 150 VAC reinforced isolation

Response time

Response time (0...90%, 100...10%).....	< 5 ms
Programming.....	PR 4500 communication interfaces
Signal dynamics, input.....	Analog signal chain
Signal dynamics, output.....	Analog signal chain
SMART bi-directional communication frequency range.....	0.5...7.5 kHz
Signal / noise ratio.....	> 60 dB
Accuracy.....	Better than 0.1% of sel. range
mA, absolute accuracy.....	≤ ±16 µA
mA, temperature coefficient.....	≤ ±1.6 µA / °C
Effect of supply voltage change on output (nom. 24 VDC).....	< ±10 µA
EMC immunity influence.....	< ±0.5% of span
Extended EMC immunity: NAMUR NE21, A criterion, burst.....	< ±1% of span

Input specifications

Current input

Measurement range.....	3.5...23 mA
2-wire transmitter supply 9106A1x.....	>16 V / 20 mA
2-wire transmitter supply 9106A2x.....	>15 V / 20 mA
Sensor error detection: Loop break 4...20 mA.....	< 1 mA
Input voltage drop, supplied unit.....	< 4 V @ 23 mA
Input voltage drop, non-supplied unit.....	< 6 V @ 23 mA

Output specifications

Current output

Signal range.....	3.5...23 mA
Load (@ current output).....	≤ 600 Ω
Load stability.....	≤ 0.01% of span / 100 Ω
Current limit.....	≤ 28 mA

Passive 2-wire mA output

Effect of external 2-wire supply voltage variation.....	< 0.005% of span / V
Max. external 2-wire supply.....	26 VDC

Status relay

Relay function.....	N.C.
Programmable low setpoint.....	0...29.9 mA
Programmable high setpoint.....	0...29.9 mA
Hysteresis for setpoints.....	0.1 mA
Max. voltage.....	125 VAC / 110 VDC
Max. current.....	0.5 AAC / 0.3 ADC
Max. voltage - hazardous installation.....	32 VDC / 32 VAC
Max. current - hazardous installation.....	1 ADC / 0.5 AAC
of span.....	= normal measurement range 4...20 mA

Observed authority requirements

EMC.....	2014/30/EU & UK SI 2016/1091
LVD.....	2014/35/EU & UK SI 2016/1101
ATEX.....	2014/34/EU & UK SI 2016/1107
RoHS.....	2011/65/EU & UK SI 2012/3032
EAC.....	TR-CU 020/2011
EAC LVD.....	TR-CU 004/2011
EAC Ex.....	TR-CU 012/2011

Approvals

ATEX.....	DEKRA 11ATEX0244 X
IECEX.....	DEK 11.0084X
UKEX.....	DEKRA 21UKEX0171X
c FM us.....	FM16US0465X / FM16CA0213X
INMETRO.....	DEKRA 23.0003X
c UL us, UL 61010-1.....	E314307
c UL us, UL 913.....	E233311 (only 9106xxx-U9)
CCC.....	2020322309003231
KCs.....	21_AV4BO_0169X (only 9106Axx-KCs)
EAC Ex.....	RU C-DK.HA65.B.00355/19
DNV Marine.....	TAA00000JD
ClassNK.....	TA24034M
SIL.....	SIL 2 / SIL 3 certified & fully assessed acc. to IEC 61508